

# What Difference Does 'Soil Type' Make . . . ?

## Numbers tell the story!



PROFESSIONAL'S NAME

CUSTOMER'S NAME

Your company name  
and contact information

Your customer's name  
and contact information

Sample Number PSA-8294

Collection Date 2011-03-31

Process Date 2011-04-07

Report Date 2011-04-09

Date of Last Liming \_\_\_\_\_

Soil Type Sandy Loam

Main Root Development 4 inches Regular Cutting Height 2.5 inches

Main Type Grasses Bluegrass, Fescue, Rye Watering Method Auto Sprinkler

Size of Lawn Area 5,000 sq.ft. Lawn Life Stage Established

Sample Notes: \_\_\_\_\_

### LABORATORY ANALYSIS and RECOMMENDATIONS

[Results reported as Parts Per Million (ppm)]

TEST	RE-SULTS	OPTIMUM RANGE	RATING	RECOMMENDATIONS
1. pH Adjustment	5.7	6.2 - 6.8	Low	Apply 40 lbs./1000 sq.ft. of Dolomitic Limestone {Pelletized form recommended}
2. Calcium (Ca)	105	275 - 437	Very Low	Apply 150 lbs./ 1000 sq.ft. of gypsum in (3) 50 lb. applications 4-6 months apart

Process Date 2011-04-07

Report Date 2011-04-09

Date of Last Liming \_\_\_\_\_

Soil Type Loam

Main Root Development 4 inches Regular Cutting Height 2.5 inches

Main Type Grasses Bluegrass, Fescue, Rye Watering Method Auto Sprinkler

Size of Lawn Area 5,000 sq.ft. Lawn Life Stage Established

Sample Notes: \_\_\_\_\_

### LABORATORY ANALYSIS and RECOMMENDATIONS

[Results reported as Parts Per Million (ppm)]

TEST	RE-SULTS	OPTIMUM RANGE	RATING	RECOMMENDATIONS
1. pH Adjustment	5.7	6.2 - 6.8	Low	Apply 60 lbs./1000 sq.ft. of Dolomitic Limestone {Pelletized form recommended} [Make 2 applications of 30 lbs./1000 sq.ft. 4-6 months apart]
2. Calcium (Ca)	105	662 - 888	Extremely Low	Apply 225 lbs./ 1000 sq.ft. of gypsum in (4) 56 lb. applications 4-6 months apart

Process Date 2011-04-07

Report Date 2011-04-09

Date of Last Liming \_\_\_\_\_

Soil Type Clay Loam

Main Root Development 4 inches Regular Cutting Height 2.5 inches

Main Type Grasses Bluegrass, Fescue, Rye Watering Method Auto Sprinkler

Size of Lawn Area 5,000 sq.ft. Lawn Life Stage Established

Sample Notes: \_\_\_\_\_

### LABORATORY ANALYSIS and RECOMMENDATIONS

[Results reported as Parts Per Million (ppm)]

TEST	RE-SULTS	OPTIMUM RANGE	RATING	RECOMMENDATIONS
1. pH Adjustment	5.7	6.2 - 6.8	Low	Apply 60 lbs./1000 sq.ft. of Dolomitic Limestone {Pelletized form recommended} [Make 2 applications of 30 lbs./1000 sq.ft. 4-6 months apart]
2. Calcium (Ca)	105	888 - 1100	Extremely Low	Apply 240 lbs./ 1000 sq.ft. of gypsum in (4) 60 lb. applications 4-6 months apart